



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.983.4

Corrigendum 1
(01/2005)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Digital sections and digital line system – Optical line
systems for local and access networks

A broadband optical access system with increased
service capability using dynamic bandwidth
assignment

Corrigendum 1

CAUTION !

PREPUBLISHED RECOMMENDATION

This prepublication is an unedited version of a recently approved Recommendation. It will be replaced by the published version after editing. Therefore, there will be differences between this prepublication and the published version.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU [had/had not] received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2005

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

**A broadband optical access system with increased service capability using
dynamic bandwidth assignment**

Summary

This corrigendum to ITU-T Rec. G.983.4 (11/2001) specifies revised code points in a divided slot to report the number of accumulated cells in T-CONT buffer. This corrigendum is applied to B-PON with DBA (Dynamic Bandwidth Assignment).

In 8.3.5.10.1.3.3 of G.983.4

This sub clause should be replaced into the following text and table.

The default minislot format is shown in Figure 16 in 8.3.5.10.1.3.2. The reported 1 byte queue length is the non-linear coded value of the actual number of cells in a T-CONT of a specific ONU/ONT. The mapping between the number of cells (the input), the 1 byte value (the code) and the decoded message (the output) is given in Table 3 as default code points. Note that the decoded output is effectively rounded up to the largest value that could have resulted in that particular code point. This property ensures that the coding error is always positive.

Table 3/G.983.4 –Non-linear coding for report field of minislot

Queue Length	Binary Input (ONU/ONT)	Coding of octet (minislot)	Binary Output (OLT)
0-127	00000000abcdefg	0abcdefg	00000000abcdefg
128-255	00000001abcdefx	10abcdef	00000001abcdef1
256-511	0000001abcdexxx	110abcde	0000001abcde111
512-1023	000001abcdxxxxx	1110abcd	000001abcd11111
1024-2047	00001abcxxxxxxx	11110abc	00001abc1111111
2048-4095	0001abxxxxxxxxx	111110ab	0001ab111111111
4096-8191	001axxxxxxxxxxx	1111110a	001a11111111111
>8191	010000000000000 : 111111111111111	11111110	011111111111111
Invalid	N/A	11111111	N/A

The code point described in Table 3 may be changed according to the service situation and the implementation of OLTs and ONUs/ONTs. However, alternative code points have not been specified in this Recommendation.

NOTE – Invalid code (0xFF) indicates that ONU/ONT cannot report the actual number of cells for the T-CONT. However, in this case, OLT recognizes arrival of minislot for the T-CONT. Although the bandwidth update mechanism in this case is out of this recommendation, LOMSi is not generated.